

The **INDUTEC® MS** Standard Systems.

INDUTEC® MS
Minimum Quantity Cooling/Lubricating System



CENTRALINE e PRODOTTI
per
LUBRIFICAZIONE MINIMALE
LUBRIFICAZIONE a GOCCIA

SQL

From Professionals. For Professionals.

The **INDUTEC® MS** Modular System.

INDUTEC® MS
Minimum Quantity Cooling/Lubricating System



Testine coassiali MENZEL: lubrificazione minimale e lubrificazione a goccia



INDUTEC® MS SD4

Coaxial spraying head for practically any application.

- External medium feed

INDUTEC® MS FD4 Z2

Even better jet concentration for increased spraying distances or for internal cooling.

- External or internal medium feed (internal cooling)
- Increased air flow rate due to a second spraying air connection
- Max. spraying air quantity approx. 180l/min**

INDUTEC® MS SD4 M2

For spraying unmixed mediums which are stored and fed to the spraying head separately.

- External medium feed
- Medium circulation with unmixed mediums
- Two different mediums

INDUTEC® MS SD3

Special spraying head with grid setting for medium and flow control valve for spraying air directly to the main spraying head body.

- External medium feed
- Medium quantity adjustable on the main body (grid)
- Spraying air quantity adjustable on the main body

